

Safety data sheet

Page: 1/14

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 04.11.2021 Version: 2.0

Product: Styrofan® PLUS 7552 X

(ID no. 30695324/SDS_GEN_00/EN)

Date of print 21.11.2021

1. Identification

Product identifier

Styrofan® PLUS 7552 X

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Raw material, for industrial use only Recommended use: Raw material, for industrial use only

Details of the supplier of the safety data sheet

Company:
BASF SE
67056 Ludwigshafen
GERMANY
Regional Business Unit Dispersions and
Resins Europe

Telephone: +49 621 60-72509 E-mail address: ed-psr@basf.com

Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

2. Hazards Identification

Classification of the substance or mixture

According to UN GHS criteria

Skin Sens. 1

Date / Revised: 04.11.2021 Version: 2.0

Product: Styrofan® PLUS 7552 X

(ID no. 30695324/SDS_GEN_00/EN)

Date of print 21.11.2021

Aquatic Acute 3 Aquatic Chronic 3

For the classifications not written out in full in this section the full text can be found in section 16.

Label elements

Globally Harmonized System (GHS)

Pictogram:



Signal Word: Warning

Hazard Statement:

H317 May cause an allergic skin reaction.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280 Wear protective gloves.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P272 Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

According to UN GHS criteria

Hazard determining component(s) for labelling: mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Other hazards

According to UN GHS criteria

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Date / Revised: 04.11.2021 Version: 2.0

Product: Styrofan® PLUS 7552 X

(ID no. 30695324/SDS_GEN_00/EN)

Date of print 21.11.2021

3. Composition/Information on Ingredients

Substances

Not applicable

Mixtures

Chemical nature

Aqueous dispersion of a polymer based on: Styrene, Buta-1,3-diene

Hazardous ingredients (GHS)

According to UN GHS criteria

mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Content (W/W): < 50 PPM Acute Tox. 3 (oral)

CAS Number: 55965-84-9 Acute Tox. 2 (Inhalation - mist)

INDEX-Number: 613-167-00-5 Acute Tox. 2 (dermal)

Skin Corr./Irrit. 1C
Eye Dam./Irrit. 1
Skin Sens. 1A
Aquatic Acute 1
Aquatic Chronic 1
M-factor acute: 100
M-factor chronic: 100

H301, H317, H314, H310 + H330, H400, H410

EUH071

Specific concentration limit:
Skin Sens. 1A: >= 0,0015 %
Eye Dam./Irrit. 1: >= 0,6 %
Eye Dam./Irrit. 2: 0,06 - < 0,6 %
Skin Corr./Irrit. 1C: >= 0,6 %

Skin Corr./Irrit. 2: 0,06 - < 0,6 %

2-Methyl-2H-isothiazol-3-one

Date / Revised: 04.11.2021 Version: 2.0

Product: Styrofan® PLUS 7552 X

(ID no. 30695324/SDS_GEN_00/EN)

Date of print 21.11.2021

Content (W/W): <= 75 PPM Acute Tox. 2 (Inhalation - dust)
CAS Number: 2682-20-4 Acute Tox. 3 (oral)

CAS Number: 2682-20-4 EC-Number: 220-239-6 INDEX-Number: 613-326-00-9

Acute Tox. 3 (dermal)
Acute Tox. 3 (dermal)
Skin Corr./Irrit. 1B
Eye Dam./Irrit. 1
Skin Sens. 1A
Aquatic Acute 1
Aquatic Chronic 1

M-factor acute: 10 M-factor chronic: 1

H330, H317, H314, H301 + H311, H400, H410

EUH071

Specific concentration limit: Skin Sens. 1A: >= 0,0015 %

1,2-Benzisothiazol-3(2H)-one

Content (W/W): <= 75 PPM CAS Number: 2634-33-5 EC-Number: 220-120-9 INDEX-Number: 613-088-00-6

Acute Tox. 4 (oral) Skin Corr./Irrit. 2 Eye Dam./Irrit. 1 Skin Sens. 1 Aquatic Acute 1 Aquatic Chronic 1 M-factor acute: 1 M-factor chronic: 1

H318, H315, H302, H317, H400, H410

Specific concentration limit: Skin Sens. 1: >= 0,05 %

For the classifications not written out in full in this section the full text can be found in section 16.

4. First-Aid Measures

Description of first aid measures

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

Date / Revised: 04.11.2021 Version: 2.0

Product: Styrofan® PLUS 7552 X

(ID no. 30695324/SDS_GEN_00/EN)

Date of print 21.11.2021

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far

Hazards: No hazards anticipated.

Indication of any immediate medical attention and special treatment needed

Treatment: Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media: water spray, dry powder, foam, carbon dioxide

Special hazards arising from the substance or mixture

No particular hazards known.

Advice for fire-fighters

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Avoid contact with skin and eyes.

Environmental precautions

Do not release untreated into natural waters.

Methods and material for containment and cleaning up

For small amounts: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose

binder, kieselguhr). Dispose of absorbed material in accordance with regulations.

For large amounts: Pump off product. For residues: Rinse away with water.

7. Handling and Storage

Precautions for safe handling

Date / Revised: 04.11.2021 Version: 2.0

Product: Styrofan® PLUS 7552 X

(ID no. 30695324/SDS_GEN_00/EN)

Date of print 21.11.2021

Handle in accordance with good industrial hygiene and safety practice. After long storage, slight quantities of carbon monoxide may be formed. To our best knowledge, the occupational exposure limit (OEL) is not exceeded during use. Entering of tanks must only be performed after intensive cleaning and when it is ensured that residual vapours have been removed. Consideration of national laws and international standards for confined space entry should be taken in to account. In case of doubt, the concentration of Carbon monoxide must be determined.

Conditions for safe storage, including any incompatibilities

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyester resin, glass reinforced (Palatal A410), Stainless steel 1.4301 (V2), Stainless steel 1.4401, enamelled, glass

Further information on storage conditions: Store protected against freezing. Avoid direct sunlight.

Protect from temperatures below: 5 °C Protect from temperatures above: 60 °C

Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

8. Exposure Controls/Personal Protection

Control parameters

Components with occupational exposure limits

55965-84-9: mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

The release and quantity of the stated substance is dependent on the processing conditions.

Exposure controls

Personal protective equipment

Hand protection:

Suitable chemical resistant safety gloves (EN ISO 374-1) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc. Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

General safety and hygiene measures

Date / Revised: 04.11.2021 Version: 2.0

Product: Styrofan® PLUS 7552 X

(ID no. 30695324/SDS_GEN_00/EN)

Date of print 21.11.2021

Hands and/or face should be washed before breaks and at the end of the shift. Avoid contact with skin and eyes.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Form: liquid, dispersion

Colour: white Odour: faint odour

Odour threshold:

No data available.

pH value: 7,0 - 9,0 (DIN ISO 976)

(25 °C)

Information on: Water

Melting point: 0 °C

Information on: Water

Boiling point: 100 °C

Flash point:

Flammability:

not applicable

Evaporation rate:

No data available. not flammable

Lower explosion limit:

For liquids not relevant for classification and labelling.

Upper explosion limit:

For liquids not relevant for classification and labelling.

Ignition temperature:

not applicable

Information on: Water

Vapour pressure:

23,4 hPa (20 °C)

Literature data.

Density: approx. 1,04 g/cm3

(ISO 2811-1)

(20 °C)

Relative density:

No data available.

Relative vapour density (air):

not applicable

Solubility in water: partly soluble

(15 °C)

Partitioning coefficient n-octanol/water (log Kow):

not applicable

Date / Revised: 04.11.2021 Version: 2.0

Product: Styrofan® PLUS 7552 X

(ID no. 30695324/SDS_GEN_00/EN)

(DIN EN ISO 3251)

Date of print 21.11.2021

Self ignition: not self-igniting

Thermal decomposition: No decomposition if used correctly.

Viscosity, dynamic: 100 - 500 mPa.s (DIN EN ISO 2555 (RVT))

(23 °C)

Explosion hazard: not explosive

Fire promoting properties: not fire-propagating

Other information

Miscibility with water:

miscible

Solids content: 51 - 53 %

Other Information:

Range of particle size: $< 0.1 \mu m - 10 \mu m$

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions. After long storage, slight quantities of carbon monoxide may be formed.

Conditions to avoid

Avoid extreme temperatures.

Incompatible materials

Substances to avoid:

No substances known that should be avoided.

Hazardous decomposition products

.

No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information

Information on toxicological effects

Acute toxicity

Date / Revised: 04.11.2021 Version: 2.0

Product: Styrofan® PLUS 7552 X

(ID no. 30695324/SDS_GEN_00/EN)

Date of print 21.11.2021

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Experimental/calculated data:

LD50 rat (oral): > 2.000 - 10.000 mg/kg

Irritation

Assessment of irritating effects:

If the product adheres to skin, irritation may occur when it dries.

Not irritating to the eyes. Not irritating to the skin. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Experimental/calculated data:

Skin corrosion/irritation rabbit: non-irritant (OECD Guideline 404)

Serious eye damage/irritation rabbit: non-irritant (OECD Guideline 405)

Respiratory/Skin sensitization

Assessment of sensitization:

May cause sensitization by skin contact.

Germ cell mutagenicity

Assessment of mutagenicity:

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity:

The whole of the information assessable provides no indication of a carcinogenic effect.

Reproductive toxicity

Assessment of reproduction toxicity:

Not expected to cause reproductive toxicity (based on composition).

Developmental toxicity

Assessment of teratogenicity:

The data available for an assessment of the effect of the substance on developmental toxicity are not sufficient for a proper evaluation.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Date / Revised: 04.11.2021 Version: 2.0

Product: Styrofan® PLUS 7552 X

(ID no. 30695324/SDS_GEN_00/EN)

Date of print 21.11.2021

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

No adverse effects were observed after repeated inhalative exposure in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Other relevant toxicity information

No data available.

12. Ecological Information

Toxicity

Toxicity to fish:

LC50 (96 h) 10 - 100 mg/l, Brachydanio rerio (OECD Guideline 203, static)

The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic invertebrates:

EC50 (48 h) 10 - 100 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)

The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic plants:

EC50 (72 h) 10 - 100 mg/l, Scenedesmus subspicatus (OECD Guideline 201)

The product has not been tested. The statement has been derived from the properties of the individual components.

Microorganisms/Effect on activated sludge:

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Chronic toxicity to fish:

LC50 (96 h) 10 - 100 mg/l, Brachydanio rerio (OECD Guideline 204, static)

The product has not been tested. The statement has been derived from the structure of the product.

Chronic toxicity to aquatic invertebrates:

EC50 (48 h) 10 - 100 mg/l, Daphnia magna (static)

The product has not been tested. The statement has been derived from the structure of the product.

Persistence and degradability

Assessment biodegradation and elimination (H2O):

Page: 11/14

Safety data sheet according to UN GHS 4th rev.

Date / Revised: 04.11.2021 Version: 2.0

Product: Styrofan® PLUS 7552 X

(ID no. 30695324/SDS_GEN_00/EN)

Date of print 21.11.2021

The product can be virtually eliminated from water by abiotic processes e.g. adsorption onto activated sludge.

Elimination information:

> 70 % DOC reduction (OECD 302B; ISO 9888; 88/302/EEC,part C) Easily eliminated from water. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Bioaccumulative potential

Bioaccumulation potential:

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

Mobility in soil

Assessment transport between environmental compartments:

Volatility: No data available.

Other adverse effects

No data available.

Additional information

Adsorbable organically-bound halogen (AOX):

No data available.

13. Disposal Considerations

Waste treatment methods

Must be disposed of or incinerated in accordance with local regulations.

A waste code in accordance with the European waste catalog (EWC) cannot be specified, due to dependence on the usage.

Observe national and local legal requirements.

14. Transport Information

Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number: Not applicable UN proper shipping name: Not applicable

Date / Revised: 04.11.2021 Version: 2.0

Product: Styrofan® PLUS 7552 X

(ID no. 30695324/SDS_GEN_00/EN)

Date of print 21.11.2021

Transport hazard class(es): Not applicable Packing group: Not applicable Not applicable Environmental hazards: Not applicable Special precautions for None known

user

RID

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

Environmental hazards: Not applicable Special precautions for None known

user

Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user:

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Air transport

Date / Revised: 04.11.2021 Version: 2.0

Product: Styrofan® PLUS 7552 X

(ID no. 30695324/SDS_GEN_00/EN)

Date of print 21.11.2021

IATA/ICAO

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable

user

Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation: Not evaluated Shipment approved: Not evaluated Pollution name: Not evaluated Pollution category: Not evaluated Ship Type: Not evaluated

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

16. Other Information

Any other intended applications should be discussed with the manufacturer.

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Skin Sens. Skin sensitization

Aquatic Acute Hazardous to the aquatic environment - acute Aquatic Chronic Hazardous to the aquatic environment - chronic

Acute Tox. Acute toxicity

Skin Corr./Irrit. Skin corrosion/irritation

Eye Dam./Irrit. Serious eye damage/eye irritation

H301 Toxic if swallowed.

H317 May cause an allergic skin reaction.

H314 Causes severe skin burns and eye damage.

H310 + H330 Fatal in contact with skin or if inhaled

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H330 Fatal if inhaled.

H301 + H311 Toxic if swallowed or in contact with skin

H318 Causes serious eye damage.

H315 Causes skin irritation.

Page: 14/14

Safety data sheet according to UN GHS 4th rev.

Date / Revised: 04.11.2021 Version: 2.0

Product: Styrofan® PLUS 7552 X

(ID no. 30695324/SDS_GEN_00/EN)

Date of print 21.11.2021

H302 Harmful if swallowed.

EUH071 Corrosive to the respiratory tract.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.